

LOA: 14.7 M / 48' 3"

## SPECIFICATIONS

Length overall w/ swim platform & protection platform	14.7 M / 48' 3"
Beam overall	7.17 M / 23' 6"
Height above waterline w/ hard top	5.70 M / 18' 8"
Draft without sacrificial skegs	1.09 M / 3' 7"
Draft with sacrificial skegs	1.12 M / 3' 8"
Light displacement	21,600 KG / 47,620 LB
Fully loaded displacement	25,200 KG / 55,556 LB
Fuel tank	1,350 L / 356 GAL
Water tank	780 L / 206 GAL
Holding tank	340 L / 90 GAL
CE certification	A:10, B:10, C:16, D:25
Sleeps (up to)	10
Max passengers	25
Cabins (up to)	4
Heads (up to)	4
Showers (up to)	5

## ENGINES

2X D4 230 HP Volvo Penta Diesel
2X D6 340 HP Volvo Penta Diesel (optional)
2X D6 380 HP Volvo Penta Diesel (optional)

## CONSTRUCTION


Resin infused hull and deck construction creating high strength and stiffness  
 Solid FRP lamination at hull centerlines including all through hulls  
 Vinyl ester resin with excellent corrosive and water resistant properties  
 NPG gelcoat with superior UV resistance  
 Resin infused bulkheads  
 All main FRP components resin infused construction including bulkheads  
 Bow crash box in each hull  
 Windows in hull and deck high quality tempered shatter proof glass meeting ISO standards  
 Custom built salon and flybridge support structure using 316 stainless steel




MAIN DECK



FLYBRIDGE



3 CABIN



4 CABIN