



#### **SPECIFICATIONS**

| Length overall w/ swim platform excl. anchor roller | 9.93 M / 32'7"       |
|---|----------------------|
| Hull length   | 8.88 M / 29' 2"      |
| Beam overall  | 3.85 M / 12' 8"      |
| Length of waterline                                 | 7.79 M / 25' 7"      |
| Height above waterline w/ hard top                  |                      |
| (excludes electrics and electronics)                | 2.66 M / 28' 8"      |
| Hull draft with outboards up                        | 64 CM / 2'1"         |
| Displacement dry                                    | 5,700 KG / 12,566 LB |
| Fully loaded displacement                           | 7,500 KG / 16,535 LB |
| CE certification                                    | B:8, C:14, D:14      |
| Sleeps (up to)                                      | 4 (2 in salon)       |
| Max passengers                                      | 14                   |
| Cabins  | 1                    |
| Heads   | 1                    |
| Showers   | 2                    |



MAIN DECK

### ENGINES

| 2X 225 HP Mercury V6 4-Stroke Outboard       |  |
|--|--|
| 2X 300 HP Mercury Verado Outboard (optional) |  |

Mercury Joystick Piloting System available (optional)

### TANKAGE

| Fuel tank (approx.)           | 2X 475 = 950 L / 2X 126 = 252 GAL |
|-------------------------------|-----------------------------------|
| Water tank standard (approx.) | 170 L / 45 GAL                    |
| Holding tank (approx.)        | 1X 80 L / 1X 21 GAL               |

## CONSTRUCTION

Resin infused hull and deck construction creating high strength and stiffness Solid FRP lamination at hull centerlines including all through hulls Vinylester resin with excellent corrosive and water resistant properties NPG gelcoat with superior UV resistance Resin infused bulkheads All main FRP components resin infused construction including bulkheads Windows in hull and deck high quality acrylic meeting ISO standards





CABIN

# CAQUILA aquilaboats.com